

PRINTER	CP1000
PRINTING SYSTEM	
Method	Dye-sublimation thermal transfer printing system
Maximum Resolution	300 x 300 dpi
Colours	3 colour inks with protective over coating, 256 levels per colour (24 bit colour depth)
MEDIA & CARTRIDGE	
Postcard Size	148 x 100 mm - KP-36IP, KP-108IN, RP-108, RP-1080V
Credit Card Size	86 x 54 mm - KC-36IP [2]
Credit Card Size Stickers	86 x 54 mm - KC-18IF [2]
Square Stickers	50 x 50 mm - KC-18IS [2]
Mini Stickers	22.0 x 17.3 mm (x8 stickers on one sheet) - KC-18IL [2]
Ink Cartridge	Included with media
Image Longevity	100 Years Print [3]
MEDIA INPUT	
Sheet Feeder	Auto feed from paper cassette
PRINT SPEEDS	
Postcard Size	approx. 47 sec [4]
Credit Card Size	approx. 27 sec [4]
Credit Card Size Stickers	approx. 27 sec [4]
Mini Stickers	approx. 27 sec [4]
PRINTING	
Print Modes	Select & Print (Selection of individual images and number of copies for batch printing),
Print Settings	All image print (Selection of all images and number of copies for batch printing),
Print Settings	DPOF Image Print,
Print Settings	ID Photo Print (Standard, Custom size, Dual),
Print Settings	Cropping
Print Settings	Print finish (Glossy, Semi-Gloss (Pattern 1/ Pattern 2/ Pattern 3)),
Print Settings	Borders (Bordered, Borderless),
Print Settings	Layout (1-up, 2-up, 4-up, 8-up, Index , Shuffle (8-up, 20-up)),
Print Settings	Image optimize (Scene detection (Blue Sky/ Sunsets), Face detection, Color cast correction on faces, iContrast, Contrast correction, Noise reduction),
Print Settings	Brightness (7 levels, from -3 to +3),
Print Settings	Smooth Skin,
Print Settings	My Colors (Vivid, Neutral, Positive Film, Sepia, B/W, Off),
Print Settings	Red-eye Correction,
Print Settings	Date,
Print Settings	ID Photo Priority, Keep Print Settings, Power saving,
Print Settings	Exif Print
PRINT METHOD	
Direct Printing From a Camera	PictBridge compliant

Direct From a Memory Card	Supported card types: CF, Microdrive, SD, SDHC, SDXC USB Flash Memory [13] Supported via an adapter [7]: miniSD, miniSDHC, microSD, microSDHC, microSDXC, xD-Picture Card
Print From a Computer	Yes, requires standard USB cable
INTERFACE	
Camera Computer LCD Monitor	USB type A port on printer USB mini-B port on printer 6.8 cm (2.7") Colour TFT viewer with multi-language user interface and tilt mechanism (Languages: English, German, French, Italian, Spanish, Russian, Simplified Chinese, Korean, Thai, Hindi, Vietnamese, Malaysian, Japanese, Portuguese, Turkish)
SUPPORTED OPERATING SYSTEM	
PC Macintosh	USB connection: Windows 8.1 / 8 / 7 SP1 USB connection: Mac OS X v10.8 - 10.9
SOFTWARE	
Browsing & Printing Drivers	SELPHY Photo Print Windows / Mac
POWER SOURCE	
AC Power Supply Battery Pack Power Consumption	Yes, supplied Yes, optional NB-CP2L (Approx. 36 Postcard size prints per full charge. Approx. 4W (standby), approx. 60W (printing)
ACCESSORIES	
Case Paper Cassette Power Supply & Battery Chargers	Print-on-the-go Bag DCC-CP3 CP Printer Carrying Case DCC-CP2 Card Size paper cassette PCC-CP400 AC Adapter CA-CP200B
PHYSICAL SPECIFICATIONS	
Operating Environment Dimensions Weight	5-40 °C, 20-80% humidity 178.0 x 135.0 x 60.5 mm (printer only without protrusions) 840g (Excluding Ink Cartridge and Paper Cassette)
<p>All data is based on Canon's standard testing methods. Subject to change without notice.</p> <p>[2] Requires optional paper cassette</p> <p>[3] To test the image permanence of prints that are stored in an album, we use an accelerated testing method similar to how the image permanence of silver-halide photo papers are measured when stored in dark places. Print samples are printed with the optical density of 1.0 (each Bk, C, M, Y). The samples are kept in a certain environment of high temperature and 50% humidity. The rate of the decrease in the optical density and rate of yellow discoloration are recorded. The recorded results are then converted to the length of time when print image is kept in an environment of 23°C/ 50% humidity. <Criteria for estimation of print longevity> 'The point where monochromatic/ reflective optical density shows loss of 30% (starting density of 1.0).</p> <p>[4] Print speed can vary dependent on data size, print method, memory card and capacity and is measured from start of printing excluding paper handling</p> <p>[7] Requires adapter (sold separately)</p> <p>[13] Irregularly sized images, or images that have been edited on a computer may not display or print. USB Devices that are not identified as "Removable media" (such as external hard drives) or do not use the FAT or exFAT file system or have GUID partition tables created on a Macintosh computer are not supported.</p>	